



## COBAstat®

### Static-dissipative anti-fatigue mat

- Durable floor mat to protect operatives from static build-up.
- Anti-fatigue standing surface for improved comfort.
- Grounded via a 10mm male stud fitted to the mat.
- Maximum performance when used with grounding wire.
- Actual resistance:  $1 \times 10^9\Omega$  to  $1 \times 10^{10}\Omega$ .

### Technical Specification

<b>Material:</b>	Virgin Closed Cell PVC Foam (Homogenous)
<b>Surface Finish:</b>	Pebble
<b>Product Height:</b>	9mm
<b>Operating Temperature:</b>	0°C to +60°C
<b>Environmental Resistance:</b>	Suitable for dry indoor environments
<b>Typical Applications:</b>	Around machinery where static build up is common. Not to be used in High Voltage Areas exceeding 240 Volts
<b>Installation Method:</b>	Loose lay
<b>Accessories:</b>	Floor Kits where required
<b>Cleaning Method:</b>	Brush or mop the top surface
<b>Flame Retardancy:</b>	Conforms to FMVSS 302. Will not burn after the ignition source is removed. When 'forced' to burn, Carbon Monoxide, Carbon Dioxide and Hydrogen Chloride fumes are emitted
<b>Country of Origin:</b>	China

Sizes	Part Code	Weight
0.6m x 0.9m	AS060001	2.00 kg
0.9m x 1.5m	AS060002	4.50 kg
0.9m x 18.3m	AS060003	55.00 kg
0.9m x per linear metre (max. 18.3m)	AS060003C	2.00 kg