

# DC50 General Purpose Dispenser

A general purpose, easy to use digital dispenser with a bright 4-digit LED display. The simple user-friendly programming enables a dispense cycle to be quickly created and automatically displayed.

The DC50 has two modes of operation.

**Manual Mode:** The dispense operation is manually controlled by a foot pedal. **Timed Mode:** Dispenses at a pre-set time for controlled, repeatable shot sizes.



### **Features**

- 1 programmable memory slot
- 0-100psi Pressure regulator gauge
- 2 dispense modes (manual & timed)
- Worldwide compatible power supply
- 4 digit LED display (0-99.99 seconds)
- Durable aluminium housing designed for industrial work environments
- Foot pedal switch & syringe stand included
- Simple, compact & easy to use design

## **Benefits**

- Digital timer control for precise & repeatable dispensing
- Adjustable vacuum suckback control prevents fluid dripping from dispense tip
- Suitable for dispensing both low and high viscosity fluids
- Industry standard air-output connector ensures universal compatability with syringe adapter heads
- Low-cost system with high reliability

# **Optional Dispensing Configurations**

#### **Finger Switch Actuated**



Item Number 560023-LFDC

### **Stand Mounted Assembly**



**Item Number** 

560021U



# DC50 Economy Dispenser





# **Specifications**

Item Number	DC50
Dimensions	7.56" x 7.17" x 3.00" (192 x 182 x 76mm)
Weight	2.14 lbs (0.97kg)
Input AC to Power Supply	100 - 240 VAC, 50/60 Hz
Cycle Rate	Up to 600 cycles / min
<b>Relative Humidity</b>	20 - 90% (No condensation)
Operating Temperature	50 - 104°F (10 - 40°C)
Timer	0.008-99.99secs
Air Input	1000psi (7 bar) max
Air Output	1-100psi (0.07-7 bar)
Standards	CE Approved, RoHS Compliant

## **Contact Us**

USA

info@fisnar.com 1 (262) 253-8600

### Europe

infoeurope@fisnar.com +44 (0) 1355 577222

#### Asia

info@fisnar.com.hk +852 2389-2827

#### India

info@fisnar.in +91-11-4556-6223-5