

SAFETY DATA SHEET according to Regulation (EU) 2020/878

# Q-No Clean Rework wand

Page 1/6

Revision 9 28

	Revision date 2023-02-28
SECTION 1: Identification of	the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Q-No Clean Rework wand
Other means of identification /	UFI No. 5XM0-94WA-N10A-T012.
UFI	
	he substance or mixture and uses advised against
Description	Soldering.
1.3. Details of the supplier of the	
Company	Qualitek Europe Ltd
Address	Unit 9 Apex Court
	Bassendale Road
	Bromborough Wirral
	CH62 3RE
Web	www.qualitek.com
Telephone	+ 44(0)151 334 0888
Fax	+ 44(0)151 334 1408
Email address of the	sales@qualitek-europe.com
competent person	
1.4. Emergency telephone numb	per
Emergency telephone number	+ 44(0)151 334 0888
	9.00 am - 5.00 pm Mon -Fri
SECTION 2: Hazards identifi	ication
2.1. Classification of the substar	nce or mixture
2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement:	[In case of inadequate ventilation] wear respiratory protection.
Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



9

Revision date 2023-02-28

Revision

2.2. Label elements	
P264 - Wash thoroughly after handling.	
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement:	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Storage	
2.3. Other hazards	
Other hazards	None.
SECTION 3: Composition/in	formation on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7	01-2119457558-25	90 - 100%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
Other(not classified)					1 - 10%	STOT SE 3: H335;

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
	of the respiratory system. Nove the exposed person to nesh an. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
	Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated
	clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.
-	DO NOT INDUCE VOMITING.

### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause dermatitis.	
Ingestion	Seek medical attention.	
4.3. Indication of any immediate medical attention and special treatment needed		

Inhalation	Coughing, difficulty in breathing and in severe cases, loss of consciousness.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Avoid prolonged or repeated exposure.	
Ingestion	DO NOT INDUCE VOMITING.	

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Carbon oxides. Alcohol resistant foam.

## 5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.



5.3. Advice for firefighters			
	Self-contained breathing apparatus. Wear protective clothing.		
SECTION 6: Accidental relea	ase measures		
6.1. Personal precautions, prote	ctive equipment and emergency procedures		
	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.		
6.2. Environmental precautions			
	Do not allow product to enter drains. Prevent further spillage if safe.		
6.3. Methods and material for containment and cleaning up			
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.		
SECTION 7: Handling and storage			
7.1. Precautions for safe handlin	g		
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.		
7.2. Conditions for safe storage,	including any incompatibilities		
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.		

# SECTION 8: Exposure controls/personal protection

8.1. Control parameters

## 8.1.1. Exposure Limit Values

Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls		
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.	
8.2.2. Individual protection measures	Wear chemical protective clothing.	
Eye / face protection	Approved safety goggles.	
Skin protection - Handprotection	Chemical resistant gloves (PVC).	
Respiratory protection	Wear suitable respiratory equipment when necessary.	
SECTION 9: Physical and chemical properties		

9.1. Information on basic physical and chemical properties



#### 9.1. Information on basic physical and chemical properties

_	
Appearance	Liquid
Colour	Clear
Odour	Alcoholic
Melting point	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	81 - 83 °C
Flash point	12 °C
Evaporation rate	1.7 g/min
Flammability (solid, gas)	Not applicable.
Upper Explosive Limit	12 %
Lower Explosive Limit	2 %
Vapour pressure	43 Pa
Relative Vapour Density	2.1 g/cm <sup>3</sup>
Fat Solubility	Not applicable.
Partition coefficient (n-octanol/water)	
Autoignition temperature	
Explosive properties	Not relevant
Oxidising properties	No data available
Solubility	Miscible in water

### 9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

## SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

tions

Oxidising agents.

10.4. Conditions to avoid

Heat, sparks and open flames.

## SECTION 11: Toxicological information

#### 11.1.4. Toxicological Information

Isopropanol	Dermal Rat LD50: 13900 mg/kg	Oral Rat LD50: 5840 mg/kg
	Dermal Rabbit LD50: 12870 mg/kg	Inhalation Rat LC50/4 h: 72.6 mg/L

#### 11.2 Information on other hazards

None.

# SECTION 12: Ecological information

## 12.1. Toxicity

Isopropanol	Algae EC50/120h: >1000 mg/L	Algae EC50/72h: >1000 mg/L
	Lepomis_Macrochirus LC50/96h: >14000000 ug/L	

SECTION 13: Disposal considerations

## General information



 Revision
 9

 Revision date
 2023-02-28

General information	
	Dispose of in compliance with all local and national regulations.
SECTION 14: Transport info	rmation
Hazard pictograms	<del>.</del>
 14.1. UN number	<u>1</u>
	UN1219
 14.2. UN proper shipping name	1
	ISOPROPANOL
 14.3. Transport hazard class(es	
ADR/RID	3
Subsidiary risk	$-\frac{1}{2}$
IMDG	3
Subsidiary risk	1-
IATA	3
Subsidiary risk	-
14.4. Packing group	
Packing group	11
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
ADR/RID	
Hazard ID	33
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-D
ΙΑΤΑ	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L
SECTION 15: Regulatory in	formation
	mental regulations/legislation specific for the substance or mixture
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
SECTION 16: Other information	ition



Other information	
Revision	<ul> <li>This document differs from the previous version in the following areas:.</li> <li>2 - Other hazards.</li> <li>2 - Hazard pictograms.</li> <li>11 - 11.2 Information on other hazards.</li> </ul>
Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

