

SAFETY DATA SHEET



according to 1907/2006/EC, Article 31

Q399-42-CLP

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	Q399-42-CLP
CAS No.	67-63-0
EC No.	200-661-7
Index No.	603-117-00-0
1.2. Relevant identified uses of the substance or mixture and uses advised against	
Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen);
Description	Soldering.
1.3. Details of the supplier of the safety data sheet	
Company	Qualitek Europe Ltd
Address	Unit 9 Apex Court Bassendale Road Bromborough Wirral CH62 3RE
Web	www.qualitek.com
Telephone	+ 44(0)151 334 0888
Fax	+ 44(0)151 334 1408
Email address of the competent person	sales@qualitek-europe.com
1.4. Emergency telephone number	
Emergency telephone number	+ 44(0)151 334 0888 9.00 am - 5.00 pm Mon -Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
2.1.1. Classification - 67/548/EEC	F; R11 Xi; R36 R67 Symbols: F: Highly flammable. Xi: Irritant.
Main hazards	Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
2.2. Label elements	
Hazard pictograms	 
Signal Word	Danger

Q399-42-CLP

Revision 1

Revision date 2015-05-07

2.2. Label elements

Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement: Prevention	P210 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking. P233 - Keep container tightly closed. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.
Precautionary Statement: Disposal	Do not empty into drains; dispose of this material and its container in a safe way.

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7	01-2119457558-25		F; R11 Xi; R36 R67
Other (Not Classified)						Xi; R36/37/38

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7	01-2119457558-25		Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
Other (Not Classified)						

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

General information

	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
--	---

Q399-42-CLP

Revision 1

Revision date 2015-05-07

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Carbon oxides. Alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

. Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Q399-42-CLP (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250

8.2. Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures Wear chemical protective clothing.

Eye / face protection Approved safety goggles.

Skin protection - Handprotection Chemical resistant gloves (PVC).

Respiratory protection Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Q399-42-CLP

Revision 1
Revision date 2015-05-07

9.1. Information on basic physical and chemical properties

State	Liquid
Colour	Clear
Odour	Alcoholic
Boiling point	82 °C
Flash point	12 °C
Upper Explosive Limit	12.5 %
Lower Explosive Limit	2.5 %
Autoignition temperature	350 °C
Solubility	Soluble in water

9.2. Other information

Specific gravity	0.825 - 0.835
------------------	---------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

Q399-42-CLP	Dermal Rat LD50: >2000	Oral Mouse LD50: >2000
-------------	------------------------	------------------------

SECTION 12: Ecological information

12.3. Bioaccumulative potential

	Does not bioaccumulate.
--	-------------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1219
--	--------

14.2. UN proper shipping name

	ISOPROPANOL
--	-------------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-

Q399-42-CLP

Revision 1

Revision date 2015-05-07

14.3. Transport hazard class(es)	
IATA	3
Subsidiary risk	-
14.4. Packing group	
Packing group	II
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
ADR/RID	
Hazard ID	33
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-D
IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L
SECTION 15: Regulatory information	
Further information	
	This Product is Classified to Regulation 1272/2008/EC(CLP).
SECTION 16: Other information	
Other information	
Revision	This document differs from the previous version in the following areas: 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Storage.
Text of risk phrases in Section 3	R11 - Highly flammable. R36/37/38 - Irritating to eyes, respiratory system and skin. R36 - Irritating to eyes. R67 - Vapours may cause drowsiness and dizziness.
Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.